

Garlock Viblonâ„ç 276 Neoprene Bearing Pad

Category : Polymer , Thermoset , Rubber or Thermoset Elastomer (TSE)

Material Notes:

Viblonâ„ç pads are technically engineered and specifically designed to cushion impact, shock and vibration. Constructed of multiple layers of high-quality, cotton-polyester duck fabric, completely impregnated with specially designed nitrile compounds. Garlock Viblonâ„ç pads provide a uniform transfer of load from beam to substructure. Designed for use in bridge, industrial machinery and railroad applications. Black, smooth finish. Information provided by Garlock Rubber Technologies

Order this product through the following link:

http://www.lookpolymers.com/polymer_Garlock-Viblon-276-Neoprene-Bearing-Pad.php

Mechanical Properties	Metric	English	Comments
Hardness, Shore A	65 - 75	65 - 75	
Tensile Strength	>= 15.5 MPa	>= 2250 psi	
	20.7 MPa	3000 psi	Typical
Elongation at Break	>= 300 %	>= 300 %	

Thermal Properties	Metric	English	Comments
Maximum Service Temperature, Air	93.3 Â°C	200 Â°F	
Minimum Service Temperature, Air	-40.0 Â°C	-40.0 Â°F	

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215, Fengxian District, Shanghai City, China