

Glastic Laminates/Shapes 2035-1 Fiberglass-Reinforced Polyester Standoff Insulator

Category : Polymer , Thermoset , Filled/Reinforced Thermoset , Polyester, TS , Thermoset Polyester Glass Filled BMC

Material Notes:

Data provided by Glastic Corporation. Molded from UL recognized molding compound. Moisture and heat resistance of Glastic Insulators are higher than those of conventional plastic insulators.

Order this product through the following link:

http://www.lookpolymers.com/polymer_Glastic-LaminatesShapes-2035-1-Fiberglass-Reinforced-Polyester-Standoff-Insulator.php

Mechanical Properties	Metric	English	Comments
Crush Resistance	11300 kg	25000 lb (mass)	Compressive Strength

Thermal Properties	Metric	English	Comments
UL RTI, Electrical	130 Â°C	266 Â°F	
UL RTI, Mechanical with Impact	130 Â°C	266 Â°F	
Flammability, UL94	V-0	V-0	

Electrical Properties	Metric	English	Comments
Arc Resistance	180 sec	180 sec	

Descriptive Properties	Value	Comments
Tensile Strength	2500 lbs.	

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China