

Glastic Laminates/Shapes UTR Pultruded Tubing, Fiberglass-Reinforced Polyester

Category : Polymer , Thermoset , Filled/Reinforced Thermoset , Polyester, TS , Thermoset Polyester Glass Filled BMC

Material Notes:

Data provided by Glastic Corporation.NEMA GPO-3, NEMA LI-1. Commonly used for tubing and fuse applications.

Order this product through the following link:

http://www.lookpolymers.com/polymer_Glastic-LaminatesShapes-UTR-Pultruded-Tubing-Fiberglass-Reinforced-Polyester.php

| Physical Properties | Metric | English | Comments |
|---------------------|--------|---------|-----------|
| Water Absorption | 0.60 % | 0.60 % | ASTM D570 |

| Thermal Properties | Metric | English | Comments |
|--------------------------------|---------|---------|------------|
| UL RTI, Electrical | 130 Â°C | 266 Â°F | UL 746B |
| UL RTI, Mechanical with Impact | 160 Â°C | 320 Â°F | UL 746B |
| Oxygen Index | 30 % | 30 % | ASTM D2862 |

| Electrical Properties | Metric | English | Comments |
|-----------------------|---------|---------|-----------|
| Arc Resistance | 150 sec | 150 sec | ASTM D495 |

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China