

## Global GAB-130 30% Glass Reinforced, General Purpose ABS

Category : Polymer , Thermoplastic , ABS Polymer , Acrylonitrile Butadiene Styrene (ABS), 30% Glass Fiber Filled

**Material Notes:**

Information provided by Global Polymers Corporation.

Order this product through the following link:

[http://www.lookpolymers.com/polymer\\_Global-GAB-130-30-Glass-Reinforced-General-Purpose-ABS.php](http://www.lookpolymers.com/polymer_Global-GAB-130-30-Glass-Reinforced-General-Purpose-ABS.php)

Physical Properties	Metric	English	Comments
Density	1.29 g/cc	0.0466 lb/in <sup>3</sup>	ASTM D792
Linear Mold Shrinkage	0.0050 cm/cm	0.0050 in/in	ASTM D955
Melt Flow	5.0 g/10 min @Load 3.60 kg, Temperature 230 °C	5.0 g/10 min @Load 7.94 lb, Temperature 446 °F	ASTM D1238

Mechanical Properties	Metric	English	Comments
Tensile Strength, Yield	86.2 MPa	12500 psi	ASTM D638
Flexural Modulus	6.34 GPa	920 ksi	ASTM D790
Izod Impact, Notched	0.641 J/cm	1.20 ft-lb/in	ASTM D256

## Contact Songhan Plastic Technology Co.,Ltd.

Website : [www.lookpolymers.com](http://www.lookpolymers.com)

Email : [sales@lookpolymers.com](mailto:sales@lookpolymers.com)

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China