

## Gouda Vuurvast ADHESIET A Dry Air-Setting Refractory Mortar

Category : Ceramic , Oxide , Aluminum Oxide , Silicon Oxide

### Material Notes:

Description: Adhesiet A is a general purpose air setting mortar, supplied as a dry powder for use up to 1400°C. Remarks: Adhesiet mortars can be stored for an unlimited time if kept dry and cool. Only clean water should be added to make the mortar ready for use. Information provided by Gouda Vuurvast.

Order this product through the following link:

[http://www.lookpolymers.com/polymer\\_Gouda-Vuurvast-ADHESIET-A-Dry-Air-Setting-Refractory-Mortar.php](http://www.lookpolymers.com/polymer_Gouda-Vuurvast-ADHESIET-A-Dry-Air-Setting-Refractory-Mortar.php)

Physical Properties	Metric	English	Comments
Particle Size	<= 500 µm	<= 500 µm	Grain Size

Thermal Properties	Metric	English	Comments
Maximum Service Temperature, Air	1400 °C	2550 °F	

Component Elements Properties	Metric	English	Comments
Al2O3	38 %	38 %	
Fe2O3	2.0 %	2.0 %	
Na2O or K2O	2.5 %	2.5 %	
SiO2	55 %	55 %	

Descriptive Properties	Value	Comments
Base Material	chamotte	
Mixing Water	23-28 liters	per 100 kgs dry material

## Contact Songhan Plastic Technology Co.,Ltd.

Website : [www.lookpolymers.com](http://www.lookpolymers.com)

Email : [sales@lookpolymers.com](mailto:sales@lookpolymers.com)

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215, Fengxian District, Shanghai City, China