

Gwent Electronic Materials C2080815P1 Silver Flexographic Ink

Category : Fluid , Metal , Other Engineering Material , Ceramic/Metallic Coating

Material Notes:

Silver conductor ink specifically designed for printing on to polymeric or paper substrates using flexographic printing. Ink can be printed at speeds up to 20m/min, with good line definition and good conductivity. Testing was carried out on a Timsons T-Flex 508 and Nilpeter FB-3300. Substrate: Polyester, PVC, BOPP, Cellophane, Paper or Cellulosic Board. Information provided by Gwent Electronic Materials Ltd.

Order this product through the following link:

http://www.lookpolymers.com/polymer_Gwent-Electronic-Materials-C2080815P1-Silver-Flexographic-Ink.php

Physical Properties	Metric	English	Comments
Solids Content	66 - 68 %	66 - 68 %	
	@Temperature 700 °C	@Temperature 1290 °F	
Viscosity	800 - 1000 cP	800 - 1000 cP	Haake VT 550 PK1.1°
	@Shear Rate 50.0 1/s, Temperature 25.0 °C	@Shear Rate 50.0 1/s, Temperature 77.0 °F	
Storage Temperature	20.0 °C	68.0 °F	sealed container

Electrical Properties	Metric	English	Comments
Volume Resistivity	0.000065 ohm-cm	0.000065 ohm-cm	printed onto 125µm PET film using 18cm ³ m ² anilox
Surface Resistivity per Square	0.025 - 0.030 ohm	0.025 - 0.030 ohm	printed onto 125µm PET film using 18cm ³ m ² anilox
	@Thickness 0.0250 mm	@Thickness 0.000984 in	
	0.15 - 0.165 ohm	0.15 - 0.165 ohm	Printed onto 125µm PET film using 18cm ³ m ² anilox
	@Thickness 0.00400 mm	@Thickness 0.000157 in	

Processing Properties	Metric	English	Comments
Shelf Life	6.00 Month	6.00 Month	

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215, Fengxian District, Shanghai City, China