

Henkel Frekote 44-NC Mold Release Agent

Category : Fluid , Lubricant

Material Notes:

A non-CFC release agent designed to provide multiple releases with no contaminating transfer. Can be used for the release of thermoplastics, thermosetting resins, boron, aramid, graphite / carbon fiber composites and fiberglass laminates. Benefits: High thermal stability Better mold utilization No mold build up High productivity Significantly lower mold maintenance costs No contaminating transfer

Order this product through the following link:

http://www.lookpolymers.com/polymer_Henkel-Frekote-44-NC-Mold-Release-Agent.php

Thermal Properties	Metric	English	Comments
Maximum Service Temperature, Air	60.0 Å°C	140 Å°F	

Processing Properties	Metric	English	Comments
Cure Time	15.0 min	0.250 hour	
	@Temperature 125 Å°C	@Temperature 257 Å°F	
	180 min	3.00 hour	
	@Temperature 25.0 Å°C	@Temperature 77.0 Å°F	

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China