

Henkel Hysol EA 9896 WPP Peel Ply

Category : Polymer , Film , Thermoplastic , Nylon

Material Notes:

Pre-impregnated, nylon peel ply product supplied in film form. Specially designed resin system capable of curing at 250°F / 121°C.

Compatible with state-of-the-art composite prepreg resin systems. Provides minimal residual peel ply fibers at the bond surface after curing and removal. Applications: Composite Surfacing Composite Bonding

Order this product through the following link:

http://www.lookpolymers.com/polymer_Henkel-Hysol-EA-9896-WPP-Peel-Ply.php

Physical Properties	Metric	English	Comments
Storage Temperature	-18.0 Â°C	-0.400 Â°F	

Thermal Properties	Metric	English	Comments
Maximum Service Temperature, Air	93.0 Â°C	199 Â°F	
Glass Transition Temp, Tg	93.0 Â°C	199 Â°F	wet
	132 Â°C	270 Â°F	dry

Processing Properties	Metric	English	Comments
Cure Time	90.0 - 120 min	1.50 - 2.00 hour	
	@Temperature 121 Â°C	@Temperature 250 Â°F	

Descriptive Properties	Value	Comments
Out-Time (days)	14	at 23Â°C

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China