

## Henkel Turco 5668 Deoxidizer

Category : Fluid , Solvent

**Material Notes:**

Turco 5668 is a diphase, liquid paint remover developed to remove resistant coatings, such as aluminized silicones, polyurethanes, acrylics, epoxies and chromated primers without using phenols, chromate, chlorinated solvents or acids. Ideal for the removal of PRC-1560M and PRC-1560MC coatings and is not detrimental to aircraft metals such as aluminum, titanium, magnesium, cadmium, conversion coatings, Dow coatings or ferrous alloys. Meets all requirements of MIL-R-83936B for removal of paint from aircraft wheels, landing gear components, and other aircraft and AGE components. Applications: Jet Engine Cleaning Aircraft Parts Cleaning

Order this product through the following link:

[http://www.lookpolymers.com/polymer\\_Henkel-Turco-5668-Deoxidizer.php](http://www.lookpolymers.com/polymer_Henkel-Turco-5668-Deoxidizer.php)

Processing Properties	Metric	English	Comments
Processing Temperature	70.0 - 80.0 °C	158 - 176 °F	
	@Time 3600 sec	@Time 1.00 hour	

Descriptive Properties	Value	Comments
Chemistry	Diphase Liquid	
Consistency	Liquid	
Form	Concentrated	
Substrate	Aluminum	
	Ferrous	
	Magnesium	
	Non-Ferrous	
	Stainless Steel	
	Titanium	

## Contact Songhan Plastic Technology Co.,Ltd.

Website : [www.lookpolymers.com](http://www.lookpolymers.com)Email : [sales@lookpolymers.com](mailto:sales@lookpolymers.com)

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215, Fengxian District, Shanghai City, China