

Heraeus Cleviosâ, ¢ S V3 Antistatic/Conductive Polymer Coating for Screen Printing

Category: Polymer

Material Notes:

Poly(3,4-ethylenedioxythiophene)poly(styrenesulfonate), provided as a paste designed for application by silk screen printing to be used for transparent conductive devices. Cleviosâ,¢ S V3 grade is the standard grade screen printing paste. Used for transparent electrodes for EL lamps, touch panels, membrane switches, and printed electronics. Features include flexibility, transparency, high conductivity, and 3-D thermoformability.Information provided by Heraeus, Conductive Polymers Division.

Order this product through the following link:

http://www.lookpolymers.com/polymer_Heraeus-Clevios-S-V3-AntistaticConductive-Polymer-Coating-for-Screen-Printing.php

Physical Properties	Metric	English	Comments
Viscosity	2500 - 3000 cP	2500 - 3000 cP	As Supplied

Optical Properties	Metric	English	Comments
Transmission, Visible	90 %	90 %	transparent; thickness not quantified

Electrical Properties	Metric	English	Comments
Surface Resistivity per Square	350 - 500 ohm	350 - 500 ohm	prints from standard 140/31 screen

Processing Properties	Metric	English	Comments
Shelf Life	6.00 Month	6.00 Month	in unopened original container
	@Temperature 5.00 - 30.0 °C	@Temperature 41.0 - 86.0 °F	

Contact Songhan Plastic Technology Co.,Ltd.

Website: www.lookpolymers.com Email: sales@lookpolymers.com

Tel: +86 021-51131842 Mobile: +86 13061808058

Skype: lookpolymers

Address: United North Road 215, Fengxian District, Shanghai City, China