

Hexcel® Redux® 122 Surface Pretreatment Protection Solution

Category : Fluid , Polymer , Adhesive

Material Notes:

The Redux 100 series is a range of resin solutions used for protecting light alloy surfaces that have been pretreated for bonding but must be stored temporarily before bonding is completed. A thin coating of solution applied to freshly pretreated and dried surfaces loses solvent rapidly at room temperature, sealing the surfaces from the atmosphere and protecting them from loss of pretreatment quality for storage periods of up to 2 months. The Redux 100 series is intended for use with associated Redux film adhesives. When used with the corresponding Redux adhesive, the surface pretreatment protection does not need to be removed or cured prior to bonding. Cleaning solution: Methyl ethyl ketone (MEK)

Order this product through the following link:

http://www.lookpolymers.com/polymer_Hexcel-Redux-122-Surface-Pretreatment-Protection-Solution.php

Physical Properties	Metric	English	Comments
Storage Temperature	0.000 °C	32.0 °F	

Processing Properties	Metric	English	Comments
Drying Temperature	71.1 °C	160 °F	
Dry Time	>= 0.500 hour	>= 0.500 hour	
Shelf Life	24.0 Month	24.0 Month	At storage temperature

Descriptive Properties	Value	Comments
Additional out life at RT (days)	60	
Color	Pink	
Corresponding Adhesive	Redux 322, 340SP	

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China