

## Hexcel® Redux® 206-NA Foaming adhesive film

Category : Polymer , Adhesive , Film

### Material Notes:

The Redux 200 series is a range of foaming adhesive films presented in sheet form. They expand during the cure cycle to fill gaps and adhere strongly to all parts of the structure with which they come into contact. Redux foaming adhesive films are compatible with Redux film adhesives. Features: High strength at temperatures from -67°F to 428°F; Less than 1% volatiles emitted during cure; Suitable for aluminum and fiber-reinforced composite sandwich constructions; Expansion ratios from 1:1.9 to 1:4.0. Application: High foaming ratio. Associated Film Adhesives: Redux 312, 335, 382H, 609, 610

Order this product through the following link:

[http://www.lookpolymers.com/polymer\\_Hexcel-Redux-206-NA-Foaming-adhesive-film.php](http://www.lookpolymers.com/polymer_Hexcel-Redux-206-NA-Foaming-adhesive-film.php)

Mechanical Properties	Metric	English	Comments
Shear Strength	2.00 MPa	290 psi	Aluminum Double Lap Shear (0.06 inch gap)
	@Temperature 80.0 °C	@Temperature 176 °F	
	3.70 MPa	536 psi	Aluminum Double Lap Shear (0.06 inch gap)
	@Temperature 22.2 °C	@Temperature 72.0 °F	

Processing Properties	Metric	English	Comments
Cure Time	60.0 min	1.00 hour	Heat up rate 10°F/min
	@Temperature 121 °C	@Temperature 250 °F	
Shelf Life	18.0 Month	18.0 Month	
	@Temperature -17.8 °C	@Temperature 0.000 °F	

## Contact Songhan Plastic Technology Co.,Ltd.

Website : [www.lookpolymers.com](http://www.lookpolymers.com)

Email : [sales@lookpolymers.com](mailto:sales@lookpolymers.com)

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215, Fengxian District, Shanghai City, China