

Hexcel® Redux® 330MWCU Epoxy film adhesives for the bonding and finishing of composites

Category : Polymer , Adhesive , Film , Thermoset , Epoxy , Epoxy Adhesive

Material Notes:

Redux 330 is a 350°F curing tough film adhesive which is ideally suited to structural bonding, composite to composite bonding, surface finishing, electromagnetic shielding and lightning strike applications. It is available with knitted nylon, matt nylon and metal foils, in a choice of weights to suit the wide range of applications. Redux 330 has excellent structural bonding performance and exceeds the requirements of BMS-8-245. Features: Ideal for composite to composite bonding (no metallic fiber); Suitable for co-cure with 350°F prepreg systems; Good structural performance and service temperature to 270°F; Low volatile content (solventless production process); Excellent environmental resistance; High toughness; Light tack and good drapability; Contains carrier for glueline thickness control and for improved adhesive handling. Applications: Shielding and Lightning Strike Protection Adhesive Foils

Order this product through the following link:

http://www.lookpolymers.com/polymer_Hexcel-Redux-330MWCU-Epoxy-film-adhesives-for-the-bonding-and-finishing-of-composites.php

| Processing Properties | Metric | English | Comments |
|-----------------------|-----------------------|-----------------------|----------|
| Shelf Life | 6.00 Month | 6.00 Month | |
| | @Temperature -17.8 °C | @Temperature 0.000 °F | |

| Descriptive Properties | Value | Comments |
|------------------------|-------------------|----------|
| Areal Weight (psf) | 0.045 | |
| Carrier/Foil | Woven Copper foil | |

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China