

Hong Kun Group UV 1130 UV Absorber

Category : Other Engineering Material , Additive/Filler for Polymer

Material Notes:

It is recommended for both solvent and water based coatings such as automotive coatings, industrial coatings and trade sales coatings. It may be used in combination with a light stabilizer of the sterically hindered amine class (LS) such as LS 292. These synergistic combinations impart superior coating protection against gloss reduction, cracking, blistering, delamination and color change. CAS No.104810-48-2, CAS No.104810-47-1 & CAS No.25322-68-3 All information provided by Hongkun Group

Order this product through the following link:

http://www.lookpolymers.com/polymer_Hong-Kun-Group-UV-1130-UV-Absorber.php

| Physical Properties | Metric | English | Comments |
|---------------------|---------------------------------------|---|----------|
| Density | 1.17 g/cc @Temperature 20.0 Â°C | 0.0423 lb/inÂ³ @Temperature 68.0 Â°F | |
| Volatiles | <= 0.20 % | <= 0.20 % | |

| Descriptive Properties | Value | Comments |
|-------------------------------|--|----------|
| Appearance | slightly yellow clear liquid | |
| Miscibility (g/100g solution) | Immiscible with water | at 20Â°C |
| | Miscible with polar and non-polar organic solvents | at 20Â°C |

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China