

## Hyosung Topilene C600HF PP

Category : Polymer , Thermoplastic , Polypropylene (PP) , Polypropylene, Film Grade

**Material Notes:**

C600HF Film Grade Butane Random Copolymer Applications: Sealable CPP/OPP Characteristics: Low seal Slip property Transparency Information provided by Hyosung Corporation

Order this product through the following link:

[http://www.lookpolymers.com/polymer\\_Hyosung-Topilene-C600HF-PP.php](http://www.lookpolymers.com/polymer_Hyosung-Topilene-C600HF-PP.php)

Physical Properties	Metric	English	Comments
Melt Flow	7.0 g/10 min	7.0 g/10 min	ASTM D1238

Mechanical Properties	Metric	English	Comments
Hardness, Rockwell R	65	65	ASTM D785
Tensile Strength, Yield	23.5 MPa	3410 psi	ASTM D638
Elongation at Break	500 %	500 %	ASTM D638
Flexural Modulus	0.686 GPa	99.6 ksi	ASTM D790
Izod Impact, Unnotched	0.735 J/cm	1.38 ft-lb/in	ASTM D256
Heat Seal Strength Initiation Temperature	125 Â°C	257 Â°F	

Thermal Properties	Metric	English	Comments
Melting Point	130 Â°C	266 Â°F	HS Method
Deflection Temperature at 0.46 MPa (66 psi)	75.0 Â°C	167 Â°F	ASTM D648
Vicat Softening Point	115 Â°C	239 Â°F	ASTM D1525

## Contact Songhan Plastic Technology Co.,Ltd.

Website : [www.lookpolymers.com](http://www.lookpolymers.com)

Email : [sales@lookpolymers.com](mailto:sales@lookpolymers.com)

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215, Fengxian District, Shanghai City, China