

ICO Polymers ICOFLOâ, ¢ 510-5003 1000 Micron EVA Powder

Category : Polymer , Thermoplastic , Ethylene Vinyl Acetate , Ethylene Vinyl Acetate; Molded/Extruded

Material Notes:

Description: ICOFLO 510-5003 is an EVA powder specifically designed to be used in the preparation of masterbatch (concentrate). By utilizing a free flowing powder as a carrier in masterbatch (instead of pellet), superior color development or additive dispersion can be achieved in the final concentrate. Key Characteristics: Good melt flow and flexibility, vinyl acetate content of 20%. Information provided by ICO Polymers.A Schulman acquired ICO, Inc. in 2010.

Order this product through the following link:

http://www.lookpolymers.com/polymer_ICO-Polymers-ICOFLO-510-5003-1000-Micron-EVA-Powder.php

Physical Properties	Metric	English	Comments	
Density	0.940 g/cc	0.0340 lb/in³	ASTM D1505	
Particle Size	>= 150 µm	>= 150 µm	pan, 7%	
	<= 1000 µm	<= 1000 µm	sieve < 5%	
Melt Index of Compound	20 g/10 min	20 g/10 min	ASTM D1238	
	@Load 2.16 kg, Temperature 190 °C	@Load 4.76 lb, Temperature 374 °F		

Mechanical Properties	Metric	English	Comments
Elongation at Break	240 %	240 %	50 mm/min; ASTM D638

Thermal Properties	Metric	English	Comments	
Melting Point	83.0 °C	181 °F	DSC; ASTM D3418	
Vicat Softening Point	49.0 °C	120 °F	ASTM D1525	

Descriptive Properties	Value	Comments
Max Dry Flow	max 37 sec/100g	ASTM

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com Email : sales@lookpolymers.com Tel : +86 021-51131842 Mobile : +86 13061808058 Skype : lookpolymers Address : United North Road 215,Fengxian District, Shanghai City,China