

ICO Polymers ICOFLOâ, ¢ 510-5005 1000 Micron EVA Powder

Category: Polymer, Thermoplastic, Ethylene Vinyl Acetate, Ethylene Vinyl Acetate; Molded/Extruded

Material Notes:

Description: ICOFLO 510-5005 is an EVA powder specifically designed to be used in the preparation of masterbatch (concentrate). By utilizing a free flowing powder as a carrier in masterbatch (instead of pellet), superior color development or additive dispersion can be achieved in the final concentrate. Key Characteristics: very high melt flow, fast melting and great flexibility, vinyl acetate content of 28%. Information provided by ICO Polymers. A Schulman acquired ICO, Inc. in 2010.

Order this product through the following link:

http://www.lookpolymers.com/polymer_ICO-Polymers-ICOFLO-510-5005-1000-Micron-EVA-Powder.php

Physical Properties	Metric	English	Comments	
Density	0.950 g/cc	0.0343 lb/in³	ASTM D1505	
Particle Size	>= 150 Âμm	>= 150 Âμm	pan, 7%	
	<= 1000 Âμm	<= 1000 Âμm	sieve < 5%	
Melt Index of Compound	150 g/10 min	150 g/10 min		
	@Load 2.16 kg, Temperature 190 °C	@Load 4.76 lb, Temperature 374 °F	ASTM D1238	

Mechanical Properties	Metric	English	Comments
Elongation at Break	720 %	720 %	50 mm/min; ASTM D638

Thermal Properties	Metric	English	Comments
Melting Point	68.0 °C	154 °F	DSC; ASTM D3418

Descriptive Properties	Value	Comments
Max Dry Flow	max 33 sec/100g	ASTM

Contact Songhan Plastic Technology Co.,Ltd.

Website: www.lookpolymers.com Email: sales@lookpolymers.com

Tel: +86 021-51131842 Mobile: +86 13061808058

Skype: lookpolymers

Address: United North Road 215, Fengxian District, Shanghai City, China