

IRPC Polimaxx Polene 1202J Polypropylene Homopolymer

Category : Polymer , Thermoplastic , Polypropylene (PP)

Material Notes:

CHARACTERISTICS: GOOD STIFFNESS, GOOD EXTRUDABILITY, HIGH IMPACT APPLICATIONS: MONOFILAMENT/YARN/SHEET EXTRUSION AND INJECTION MOLDING COARSE TEXTILE FOR JUMBO BAGS, ROPES, STRAWS, SHEETS, INDUSTRIAL CONTAINERS, STRETCH TAPE, CLOSURES

Order this product through the following link:

http://www.lookpolymers.com/polymer_IRPC-Polimaxx-Polene-1202J-Polypropylene-Homopolymer.php

Physical Properties	Metric	English	Comments
Melt Flow	3.0 g/10 min @Load 2.16 kg, Temperature 230 Â°C	3.0 g/10 min @Load 4.76 lb, Temperature 446 Â°F	ASTM D1238

Mechanical Properties	Metric	English	Comments
Hardness, Rockwell R	107	107	ASTM D785
Tensile Strength, Yield	37.0 MPa	5370 psi	ASTM D638
Elongation at Yield	27.5 %	27.5 %	ASTM D638
Flexural Modulus	1.60 GPa	232 ksi	1% Secant; ASTM D790
Charpy Impact, Notched	0.500 J/cmÂ² @Temperature 23.0 Â°C	2.38 ft-lb/inÂ² @Temperature 73.4 Â°F	DIN 53453

Thermal Properties	Metric	English	Comments
Heat Distortion Temperature	110 Â°C	230 Â°F	ASTM D648

Processing Properties	Metric	English	Comments
Processing Temperature	200 - 280 Â°C	392 - 536 Â°F	

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China