

IRPC Polimaxx Polene PE250N Polypropylene Wax

Category : Polymer , Thermoplastic , Polypropylene (PP)

Material Notes:

APPLICATIONS: CARRIER FOR PIGMENT CONCENTRATES, LUBRICANT FOR PLASTICS, RUBBER EXTRUSION, HOT MELT ADHESIVE, PAPER COATING

Order this product through the following link:

http://www.lookpolymers.com/polymer_IRPC-Polimaxx-Polene-PE250N-Polypropylene-Wax.php

| Physical Properties | Metric | English | Comments |
|---------------------|--------------------|------------------------------------|------------|
| Density | 0.900 - 0.930 g/cc | 0.0325 - 0.0336 lb/in ³ | TPI Method |
| Viscosity | 101 - 300 cP | 101 - 300 cP | ASTM D445 |

| Mechanical Properties | Metric | English | Comments |
|---------------------------|--------------------------------------|-----------------------------------|------------|
| Penetration P(0), 1/10 mm | 3.0 - 20 @Temperature 25.0 Â°C | 3.0 - 20 @Temperature 77.0 Â°F | ASTM D1321 |

| Thermal Properties | Metric | English | Comments |
|--------------------|---------------|---------------|-----------|
| Melting Point | 108 - 124 Â°C | 226 - 255 Â°F | ASTM D127 |

| Descriptive Properties | Value | Comments |
|------------------------|------------|----------|
| Color | Pale-White | |
| Product Form | Flake | |

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China