

## ITW Devcon 10 minute,ç Epoxy, Black

Category : Polymer , Adhesive , Thermoset , Epoxy

**Material Notes:**

Information provided by ITW Devcon

Order this product through the following link:

[http://www.lookpolymers.com/polymer\\_ITW-Devcon-10-minute-Epoxy-Black.php](http://www.lookpolymers.com/polymer_ITW-Devcon-10-minute-Epoxy-Black.php)

Physical Properties	Metric	English	Comments
Viscosity	90000 cP	90000 cP	Mixed Viscosity

Mechanical Properties	Metric	English	Comments
Elongation at Break	5.0 %	5.0 %	
Adhesive Bond Strength	16.5 MPa	2400 psi	lap shear (on grit blasted steel, bond line thickness of 0.010"); ASTM D1002
Tensile Impact Strength	21.0 kJ/m <sup>2</sup>	10.0 ft-lb/in <sup>2</sup>	
Peel Strength	3.51 - 4.38 kN/m	20.0 - 25.0 pli	

Thermal Properties	Metric	English	Comments
Maximum Service Temperature, Air	93.3 Â°C	200 Â°F	dry
Minimum Service Temperature, Air	-55.0 Â°C	-67.0 Â°F	dry

Processing Properties	Metric	English	Comments
Cure Time	10.0 min	0.167 hour	Working time
	20.0 min	0.333 hour	Fixture time
	90.0 min	1.50 hour	Functional cure

Descriptive Properties	Value	Comments
Mix ratio (Resin:Hardener)	1:1	

## Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215, Fengxian District, Shanghai City, China