

Ineos ABS TRIAX® 1408 GF ABS/Nylon Blend, Injection Grade, As Conditioned (discontinued **)

Category : Polymer , Thermoplastic , ABS Polymer , Acrylonitrile Butadiene Styrene (ABS)/Nylon Blend , Nylon

Material Notes:

Standard injection molding grade, easy flow, easy mold release, fast setting. Applications: Thin walled engineering parts. Automotive sector: air filters, switch and connector parts for car electric. Electrical sector: switch and connector parts. Information provided by Bayer. LANXESS was spun-off from Bayer in early 2005. Business renamed Ineos ABS after INEOS acquires a majority shareholding under a JV with Lanxess in 2007. Subsequently Ineos acquired 100% of Ineos ABS.

Order this product through the following link:

http://www.lookpolymers.com/polymer_ineos-ABS-TRIAx-1408-GF-ABS-Nylon-Blend-Injection-Grade-As-Conditioned-nbspdiscontinued.php

Physical Properties	Metric	English	Comments
Density	1.12 g/cc	0.0405 lb/in ³	Dry As Molded

Mechanical Properties	Metric	English	Comments
Elongation at Break	10 %	10 %	
Charpy Impact Unnotched	0.600 J/cm ² @Temperature -30.0 °C	2.86 ft-lb/in ² @Temperature -22.0 °F	
Charpy Impact, Notched	1.60 J/cm ²	7.61 ft-lb/in ²	

Thermal Properties	Metric	English	Comments
Deflection Temperature at 0.46 MPa (66 psi)	117 °C	243 °F	
Deflection Temperature at 1.8 MPa (264 psi)	96.0 °C	205 °F	

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215, Fengxian District, Shanghai City, China