

Ineos Nova S-4122 Medium Impact Compact Polystyrene (discontinued **)

Category : Polymer , Thermoplastic , Polystyrene (PS)

Material Notes:

Low friction, medium impact polystyrene which combines excellent flow characteristics with a good dimensional stability under heat and a high stiffness. This grade is designed for injection molding of technical parts. All mechanical properties measured under standard conditions 50% RH and 23°C. Information provided by NOVA Chemicals. INEOS NOVA began October 1 2007 as an expansion of the 50:50 joint venture between NOVA Chemicals and INEOS to include North American assets.

Order this product through the following link:

http://www.lookpolymers.com/polymer_ineos-Nova-S-4122-Medium-Impact-Compact-Polystyrene-nbspdiscontinued-.php

Physical Properties	Metric	English	Comments
Density	1.05 g/cc	0.0379 lb/in ³	DIN 53479
Water Absorption	<= 0.10 %	<= 0.10 %	DIN 53495
Melt Flow	7.5 g/10 min @Load 5.00 kg, Temperature 200 °C	7.5 g/10 min @Load 11.0 lb, Temperature 392 °F	DIN 5375/ISO 1133

Mechanical Properties	Metric	English	Comments
Izod Impact, Notched (ISO)	5.00 kJ/m ²	2.38 ft-lb/in ²	DIN 53453/ISO 179

Thermal Properties	Metric	English	Comments
CTE, linear	80.0 µm/m-°C @Temperature 20.0 °C	44.4 µin/in-°F @Temperature 68.0 °F	DIN 53752
Thermal Conductivity	0.160 W/m-K	1.11 BTU-in/hr-ft ² -°F	DIN 52612
Vicat Softening Point	92.0 °C	198 °F	DIN 53460

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215, Fengxian District, Shanghai City, China