

## Ineos Nova T443C Expandable Polystyrene

Category : Polymer , Thermoplastic , Polystyrene (PS) , Expanded Polystyrene (EPS)

### Material Notes:

A fast expanding regular molding grade consisting of spherical polystyrene beads containing pentane as expansion agent typically used for low and standard density foam. Applications: This grade is used mainly for producing of low and standard density block, which are subsequently cut to boards for thermal insulation. Information provided by NOVA Chemicals.

Order this product through the following link:

[http://www.lookpolymers.com/polymer\\_ineos-Nova-T443C-Expandable-Polystyrene.php](http://www.lookpolymers.com/polymer_ineos-Nova-T443C-Expandable-Polystyrene.php)

Physical Properties	Metric	English	Comments
Bulk Density	0.620 g/cc	0.0224 lb/in <sup>3</sup>	
Density	0.00900 - 0.0140 g/cc	0.000325 - 0.000506 lb/in <sup>3</sup>	Normal molded density assuming cost optimized selection of processing conditions.
	>= 0.0130 g/cc	>= 0.000470 lb/in <sup>3</sup>	Minimum achievable; Single stage pre-expansion in continuous expander at atmospheric pressure
Bead Size	1.00 - 1.40 mm	0.0394 - 0.0551 in	
	0.710 - 1.70 mm	0.0280 - 0.0669 in	> 95% in this range per Berre Laboratory Analytical Methods 0492

Chemical Properties	Metric	English	Comments
Styrene Content	<= 0.10 %	<= 0.10 %	Residual Styrene Monomer Content per Berre Laboratory Analytical Methods 0075
Blowing Agent Content	>= 6.0 %	>= 6.0 %	

## Contact Songhan Plastic Technology Co.,Ltd.

Website : [www.lookpolymers.com](http://www.lookpolymers.com)

Email : [sales@lookpolymers.com](mailto:sales@lookpolymers.com)

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215, Fengxian District, Shanghai City, China