

Ineos T50-800 HDPE

Category : Polymer , Thermoplastic , Polyethylene (PE) , HDPE

Material Notes:

T50-800 is a high density polyethylene copolymer having a narrow molecular weight distribution. It is intended for injection molding applications where a good balance of processability and end-use properties are required. This material meets the Food and Drug Administration requirements of 21CFR 177.1520.

Order this product through the following link:

http://www.lookpolymers.com/polymer_ineos-T50-800-HDPE.php

Physical Properties	Metric	English	Comments
Density	0.953 g/cc	0.0344 lb/in ³	ASTM D4883
Environmental Stress Crack Resistance	5.0 hour	5.0 hour	Condition B, 10%, F50; ASTM D1693
Melt Flow	8.0 g/10 min @Load 2.16 kg, Temperature 190 °C	8.0 g/10 min @Load 4.76 lb, Temperature 374 °F	ASTM D1238

Mechanical Properties	Metric	English	Comments
Hardness, Shore D	65	65	ASTM D2240
Tensile Strength, Yield	26.9 MPa	3900 psi	2 in/min (50 mm/min); ASTM D-638
Elongation at Break	<= 600 %	<= 600 %	2 in/min (50 mm/min); ASTM D-638
Flexural Modulus	1.276 GPa	185.1 ksi	Tangent-Method 1; ASTM D790
Izod Impact, Notched	0.580 J/cm	1.09 ft-lb/in	ASTM D256

Thermal Properties	Metric	English	Comments
Deflection Temperature at 0.46 MPa (66 psi)	77.0 °C	171 °F	ASTM D648
Vicat Softening Point	128 °C	262 °F	ASTM D1525
Brittleness Temperature	<= -76.0 °C	<= -105 °F	ASTM D746

Descriptive Properties	Value	Comments
Process	Injection Molding	
Region	US & Canada	Bamberger Polymers Distribution

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China