

Ineos T60-800 HDPE

Category : Polymer , Thermoplastic , Polyethylene (PE) , HDPE

Material Notes:

Ineos T60-800 is a high density polyethylene homopolymer. This narrow molecular weight distribution resin is a product of Ineos' innovative technology. Parts fabricated from this material exhibit a glossy surface finish, and have good impact strength and rigidity. This material meets the Food and Drug Administration requirements of 21CFR 177.1520.

Order this product through the following link:

http://www.lookpolymers.com/polymer_ineos-T60-800-HDPE.php

Physical Properties	Metric	English	Comments
Density	0.961 g/cc	0.0347 lb/in ³	ASTM D4883
Environmental Stress Crack Resistance	3.0 hour	3.0 hour	Condition B, 10%, F50; ASTM D1693
Melt Flow	8.0 g/10 min @Load 2.16 kg, Temperature 190 °C	8.0 g/10 min @Load 4.76 lb, Temperature 374 °F	ASTM D1238

Mechanical Properties	Metric	English	Comments
Hardness, Shore D	65	65	ASTM D2240
Tensile Strength, Yield	31.0 MPa	4500 psi	2 in/min (50 mm/min); ASTM D-638
Elongation at Break	>= 600 %	>= 600 %	2 in/min (50 mm/min); ASTM D-638
Flexural Modulus	1.552 GPa	225.1 ksi	Tangent-Method 1; ASTM D790
Izod Impact, Notched	0.530 J/cm	0.993 ft-lb/in	ASTM D256

Thermal Properties	Metric	English	Comments
Deflection Temperature at 0.46 MPa (66 psi)	87.0 °C	189 °F	ASTM D648
Vicat Softening Point	128 °C	262 °F	ASTM D1525
Brittleness Temperature	<= -75.0 °C	<= -103 °F	ASTM D746

Descriptive Properties	Value	Comments
Process	Injection Molding	
Region	US & Canada	Bamberger Polymers Distribution

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215, Fengxian District, Shanghai City, China