

Iran Petrochemical (PCC) 52518 High Density Polyethylene

Category : Polymer , Thermoplastic , Polyethylene (PE) , HDPE , High Density Polyethylene (HDPE), Injection Molded

Material Notes:

52518 is a HDPE copolymer for injection molding applications requiring a good balance between easy of process, flow and mechanical properties. Application: housewares, high fluidity, injection molding grade. Information provided by Iran Petrochemical Commercial Co.

Order this product through the following link:

http://www.lookpolymers.com/polymer_Iran-Petrochemical-PCC-52518-High-Density-Polyethylene.php

Physical Properties	Metric	English	Comments
Density	0.952 g/cc	0.0344 lb/in ³	ASTM D1505
Melt Flow	18 g/10 min @Load 2.16 kg, Temperature 190 °C	18 g/10 min @Load 4.76 lb, Temperature 374 °F	ASTM D1238

Mechanical Properties	Metric	English	Comments
Flexural Modulus	1.35 GPa	196 ksi	ASTM D790
Izod Impact, Notched	0.250 J/cm	0.468 ft-lb/in	ASTM D256/A

Thermal Properties	Metric	English	Comments
Vicat Softening Point	122 °C	252 °F	ASTM D1525

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215, Fengxian District, Shanghai City, China