

Iran Petrochemical (PCC) PVC-S7054 Poly Vinyl Chloride

Category: Polymer, Thermoplastic, Vinyl (PVC), PVC, Flexible Grade

Material Notes:

Grade S-7054 has high porosity. Therefore it is most suitable for flexible applications. The electrical, mechanical & thermal properties expected of the various applications can be achieved with this grade. Applications: extrusion of flexible sections and hoses, cable industryInformation provided by Iran Petrochemical Commercial Co.

Order this product through the following link:

http://www.lookpolymers.com/polymer_Iran-Petrochemical-PCC-PVC-S7054-Poly-Vinyl-Chloride.php

| Physical Properties | Metric | English | Comments |
|---------------------|-------------------|---------------|------------------------------------|
| Bulk Density | 0.490 g/cc | 0.0177 lb/in³ | DIN-53466 |
| Volatiles | <= 0.20 % | <= 0.20 % | weight %; ISO R-1269 |
| Viscosity Test | 105 cm³/g | 105 cm³/g | DIN-53726 |
| Ash | <= 0.050 % | <= 0.050 % | Sulfate ash, weight %; DIN-53568/2 |

| Component Elements Properties | Metric | English | Comments |
|-------------------------------|--------|---------|-----------|
| Chlorine, Cl | 56 % | 56 % | by weight |

| Descriptive Properties | Value | Comments |
|--------------------------------------|-------|-------------------------|
| Dark Resin, particles | 30 | per 250 g PVC; HULS-6.9 |
| K-Value | 70 | DIN-53726 |
| Residual Vinyl Chloride Monomer, ppm | =1 | HULS-6.11 |

Contact Songhan Plastic Technology Co.,Ltd.

Website: www.lookpolymers.com Email: sales@lookpolymers.com

Tel: +86 021-51131842 Mobile: +86 13061808058

Skype: lookpolymers

Address: United North Road 215, Fengxian District, Shanghai City, China