

Iran Petrochemical (PCC) V 30 S Polypropylene

Category : Polymer , Thermoplastic , Polypropylene (PP) , Polypropylene, Extrusion Grade , Polypropylene, Fiber Grade

Material Notes:

V 30 S is a high fluidity PP for the protection of staple fibers with improved thermo bonding ability for no woven fabrics. Application: the typical application of this grade are cover stock for diapers, feminine care product and wipes ,filters and fabrics for the clothing and furniture industry. Information provided by Iran Petrochemical Commercial Co.

Order this product through the following link:

http://www.lookpolymers.com/polymer_Iran-Petrochemical-PCC-V-30-S-Polypropylene.php

Physical Properties	Metric	English	Comments
Density	0.900 g/cc	0.0325 lb/in ³	ISO 1183
Melt Flow	16 g/10 min	16 g/10 min	ISO 1133

Mechanical Properties	Metric	English	Comments
Tensile Stress	30.0 MPa	4350 psi	ISO R527
Elongation at Yield	12 %	12 %	ISO R527
Flexural Modulus	1.55 GPa	225 ksi	ISO 178

Thermal Properties	Metric	English	Comments
Vicat Softening Point	154 Â°C	309 Â°F	ISO 306/A
Heat Distortion Temperature	95.0 Â°C	203 Â°F	ISO 75/B

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China