

Isoflon Tisoflon® 3 AD Polytetrafluoroethylene Coated Glass Fabric

Category : Ceramic , Glass , Glass Fiber , Polymer , Thermoplastic , Fluoropolymer , PTFE , Polytetrafluoroethylene (PTFE), Glass Filled, Molded

Material Notes:

PTFE coated glass fabric one side adhesive TISOFLON® - Standard grade Information provided by Isoflon.

Order this product through the following link:

http://www.lookpolymers.com/polymer_Isoflon-Tisoflon-3-AD-Polytetrafluoroethylene-Coated-Glass-Fabric.php

Physical Properties	Metric	English	Comments
Thickness	70.0 microns	2.76 mil	
Coating Weight	130 g/m ²	81.3 lb/ream	entire thickness; NF EN ISO 2286.2

Mechanical Properties	Metric	English	Comments
Tear Strength	12.0 - 16.0 kN/m	68.5 - 91.3 pli	NF EN ISO 1421

Thermal Properties	Metric	English	Comments
Maximum Service Temperature, Air	260 °C	500 °F	
Minimum Service Temperature, Air	-150 °C	-238 °F	

Electrical Properties	Metric	English	Comments
Dielectric Strength	3.00 kV/mm	76.2 kV/in	NF EN 60243.1

Descriptive Properties	Value	Comments
PTFE Content (%)	61	

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China