

## KKPC KOSYN KTR 301 Thermoplastic Elastomer (TPE)

Category : Polymer , Thermoplastic , Elastomer, TPE , Styrenic TPE

### Material Notes:

Thermoplastic Elastomer (TPE) Characteristics: KOSYN KTR101 is linear block copolymer made by solution polymerization which polymerizes butadiene and styrene in organic solvent. It is thermoplastics free of vulcanization and has superior tensile strength and elasticity. Applications: Asphalt roofing, waterproof agent, modifier and adhesives. Additional Notes: Bound Styrene: 40% Volatile Matter: 0.5%; ASTM D1416 Ash Content: 0.15%; ASTM D1416 This product is so sensitive to sunlight and humidity that it can be tarnished and caused deterioration of quality if exposed. It is recommended to store it in cool and shady area lest it should be exposed to direct sunlight. Do not expose to incompatible materials or contaminants. Data provided by Korea Kumho Petrochemical Co., Ltd.

Order this product through the following link:

[http://www.lookpolymers.com/polymer\\_KKPC-KOSYN-KTR-301-Thermoplastic-Elastomer-TPE.php](http://www.lookpolymers.com/polymer_KKPC-KOSYN-KTR-301-Thermoplastic-Elastomer-TPE.php)

Physical Properties	Metric	English	Comments
Density	0.940 g/cc	0.0340 lb/in <sup>3</sup>	ISO 2781
Melt Flow	6.0 g/10 min @Load 5.00 kg, Temperature 200 °C	6.0 g/10 min @Load 11.0 lb, Temperature 392 °F	ASTM D1238

Mechanical Properties	Metric	English	Comments
Hardness, Shore A	61	61	5 sec; ASTM D2240
Tensile Strength, Ultimate	17.0 MPa	2470 psi	ASTM D412
Elongation at Break	900 %	900 %	ASTM D412
Modulus of Elasticity	0.0220 GPa	3.19 ksi	ASTM D412

## Contact Songhan Plastic Technology Co.,Ltd.

Website : [www.lookpolymers.com](http://www.lookpolymers.com)

Email : [sales@lookpolymers.com](mailto:sales@lookpolymers.com)

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215, Fengxian District, Shanghai City, China