

KYDEX® 331/331d Co-Extruded High Impact Fire Rated Thermoplastic Sheet with Weatherable Acrylic Film Cap

Category: Polymer, Film, Thermoplastic

Material Notes:

KYDEX® 331 is a co-extruded high impact fire rated thermoplastic sheet with a weatherable cap that offers superior performance for thermoforming. It can also be used as an impact resistant surface material.KYDEX® 331d offers the same benefits as KYDEX® 331 but with a decorative cap (black/white, granite).Features:Weatherable formulaHigh impact resistanceFire retardant, self-extinguishingLow moisture absorption, resistance to chipping and cracking, great fabrication and machining properties and flexibilityExcellent forming properties, uniform wall thickness and crisp detailCan be drilled, punched and cut using standard woodworking or metal working toolsSuggested Applications:Kiosk HousingsEquipment HousingsMedical ProductsInformation provided by Kydex, LLC.

Order this product through the following link:

http://www.lookpolymers.com/polymer_KYDEX-331331d-Co-Extruded-High-Impact-Fire-Rated-Thermoplastic-Sheet-with-Weatherable-Acrylic-Film-Cap.php

Physical Properties	Metric	English	Comments
Specific Gravity	1.35 g/cc	1.35 g/cc	ASTM D792

Mechanical Properties	Metric	English	Comments
Tensile Strength	42.0 MPa	6090 psi	ASTM D638
Flexural Strength	66.0 MPa	9570 psi	ASTM D790
Flexural Modulus	2.482 GPa	360.0 ksi	ASTM D790
Izod Impact, Notched	6.40 J/cm	12.0 ft-lb/in	ASTM D256

Thermal Properties	Metric	English	Comments
Deflection Temperature at 1.8 MPa (264 psi)	66.7 °C	152 °F	unannealed; ASTM D648
	75.5 °C	168 °F	annealed; ASTM D648
Flammability, UL94	V-0	V-0	
	5VA	5VA	

Contact Songhan Plastic Technology Co.,Ltd.

Website: www.lookpolymers.com Email: sales@lookpolymers.com

Tel: +86 021-51131842 Mobile: +86 13061808058

Skype: lookpolymers



Address: United North Road 215, Fengxian District, Shanghai City, China