

KYDEX® XD 03 Integral Pearlescent Thermoplastic Sheet for Flat Lamination and Membrane Pressed Uses

Category : Polymer , Thermoplastic

Material Notes:

Features: Thicknesses from 0.76 mm to 1.02 mm
Chemical resistant - easy to clean with aggressive cleaners
Crisp detail, minimal rejects
Can be formed on all standard presses and cut on all standard die-cutting machines
Secondary operations include: machining, sawing, blanking, punching
Suggested Applications: Store fixtures
Checkout counters
Exhibits and displays
Wainscot
Transaction surfaces
Workstations
Logo and trademark panels
Kiosks
Cabinetry
Door and drawer fascias
Pedestals and stands
Gondolas
Tabletops
Flat laminated panels
Information provided by Kydex, LLC.

Order this product through the following link:

http://www.lookpolymers.com/polymer_KYDEX-XD-03-Integral-Pearlescent-Thermoplastic-Sheet-for-Flat-Lamination-and-Membrane-Pressed-Uses.php

Descriptive Properties	Value	Comments
Ball Impact Resistance	> 3000	NEMA LD3.8
Cleanability	No Effect	NEMA LD3.4
Dart Impact Resistance	> 1075 mm	NEMA LD3.9
Surface Burning Characteristics: Flame Spread/Smoke	Class 1/A	ASTM E84
Wear Resistance	3700 cycles	NEMA LD3.13

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215, Fengxian District, Shanghai City, China