

Kazanorgsintez 108-76 Film Grade Composition of High Density Polyethylene

Category : Polymer , Film , Thermoplastic , Polyethylene (PE) , HDPE , High Density Polyethylene (HDPE), Film Grade

Material Notes:

Production Method: Based on polyethylene grades 10803-20, 15803-20, 15813-020,17504-006. Application: Designed for packing manufacture for milk and milk products.Information Provided by Kazanorgsintez

Order this product through the following link:

http://www.lookpolymers.com/polymer_Kazanorgsintez-108-76-Film-Grade-Composition-of-High-Density-Polyethylene.php

Physical Properties	Metric	English	Comments
Melt Flow	1.7 - 2.3 g/10 min	1.7 - 2.3 g/10 min	±12%

Mechanical Properties	Metric	English	Comments
Tensile Strength, Yield	>= 8.80 MPa	>= 1280 psi	
Elongation at Break	>= 400 %	>= 400 %	
Coefficient of Friction, Static	0.10 - 0.25	0.10 - 0.25	
Tear Strength Test	>= 11.3	>= 11.3	MPa

Descriptive Properties	Value	Comments
Amount of impurities [pcs]	10	
	25	to 1m2 of film, from .5 to 1.0 mm incl
	5	to 1m2 of film, over 1.0 to 2.0 mm incl

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China