

Kazanorgsintez 293-285 High Density Polyethylene Composite, Film Grade

Category : Polymer , Film , Thermoplastic , Polyethylene (PE) , HDPE , High Density Polyethylene (HDPE), Extruded , High Density Polyethylene (HDPE), Film Grade

Material Notes:

Production Method: Compositions are achieved by ethylene copolymerization by gaseous-phase method at low pressure using complex catalysts on carrier material. Application: HDPE compositions are intended to be reprocessed by extrusion method into film, used for packing of cold food, and for other purposes. Information Provided by Kazanorgsintez

Order this product through the following link:

http://www.lookpolymers.com/polymer_Kazanorgsintez-293-285-High-Density-Polyethylene-Composite-Film-Grade.php

Physical Properties	Metric	English	Comments
Density	0.943 - 0.949 g/cc	0.0341 - 0.0343 lb/in ³	
Volatiles	<= 0.10 %	<= 0.10 %	
Melt Flow	0.40 - 0.70 g/10 min	0.40 - 0.70 g/10 min	Â±18%
Ash	<= 0.060 %	<= 0.060 %	

Mechanical Properties	Metric	English	Comments
Elongation at Break	>= 450 %	>= 450 %	

Descriptive Properties	Value	Comments
Amount of impurities [pcs]	15	

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China