

## Kazanorgsintez 294-73 High Density Polyethylene Composite

Category : Polymer , Thermoplastic , Polyethylene (PE) , HDPE , High Density Polyethylene (HDPE), Injection Molded

### Material Notes:

Production Method: Compositions are achieved by ethylene copolymerization by gaseous-phase method at low pressure using complex catalysts on carrier material. Application: Composition of HD grade 294-73 is intended for injection molding and production of large-size technical items of mass exceeding 250 g and household general items. Information Provided by Kazanorgsintez

Order this product through the following link:

[http://www.lookpolymers.com/polymer\\_Kazanorgsintez-294-73-High-Density-Polyethylene-Composite.php](http://www.lookpolymers.com/polymer_Kazanorgsintez-294-73-High-Density-Polyethylene-Composite.php)

Physical Properties	Metric	English	Comments
Density	0.958 - 0.964 g/cc	0.0346 - 0.0348 lb/in <sup>3</sup>	
Volatiles	<= 0.10 %	<= 0.10 %	
Melt Flow	17 - 25 g/10 min	17 - 25 g/10 min	Â±15%
Ash	<= 0.050 %	<= 0.050 %	

Descriptive Properties	Value	Comments
Amount of impurities [pcs]	25	

## Contact Songhan Plastic Technology Co.,Ltd.

Website : [www.lookpolymers.com](http://www.lookpolymers.com)

Email : [sales@lookpolymers.com](mailto:sales@lookpolymers.com)

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China