

## Kazanorgsintez E-11 Petroleum Resin

Category : Other Engineering Material , Additive/Filler for Polymer

### Material Notes:

Production Method: Obtained as a by-product in the process of hydrocarbon gas pyrolysis on ethylene production plants. Application: Feedstock for production of motor fuel, solvents and aromatic hydrocarbons. Information Provided by Kazanorgsintez

Order this product through the following link:

[http://www.lookpolymers.com/polymer\\_Kazanorgsintez-E-11-Petroleum-Resin.php](http://www.lookpolymers.com/polymer_Kazanorgsintez-E-11-Petroleum-Resin.php)

Physical Properties	Metric	English	Comments
Density	$\geq 0.750 \text{ g/cc}$ @Temperature 20.0 °C	$\geq 0.0271 \text{ lb/in}^3$ @Temperature 68.0 °F	

Thermal Properties	Metric	English	Comments
Boiling Point	$\geq 30.0 \text{ }^{\circ}\text{C}$	$\geq 86.0 \text{ }^{\circ}\text{F}$	Initial
	$\leq 220 \text{ }^{\circ}\text{C}$	$\leq 428 \text{ }^{\circ}\text{F}$	End

Component Elements Properties	Metric	English	Comments
Free Water	$\leq 1.0 \%$	$\leq 1.0 \%$	

Descriptive Properties	Value	Comments
Appearance	Liquid of light-yellow to brown color, free of mechanical impurities	
Mass Content (%)	30	Mass content of benzene
	50	Mass content of aromatic hydrocarbons (C6-C8)
Volume ratio of fraction, in strippant up to 185°C (%)	30	

## Contact Songhan Plastic Technology Co.,Ltd.

Website : [www.lookpolymers.com](http://www.lookpolymers.com)

Email : [sales@lookpolymers.com](mailto:sales@lookpolymers.com)

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215, Fengxian District, Shanghai City, China