

Kazanorgsintez E-17 Petroleum Resin

Category: Other Engineering Material, Additive/Filler for Polymer

Material Notes:

Production Method: Obtained as a by-product in the process of hydrocarbon gas pyrolysis on ethylene production plants. Application:

Feedstock for production of motor fuel, solvents and aromatic hydrocarbons. Information Provided by Kazanorgsintez

Order this product through the following link:

http://www.lookpolymers.com/polymer_Kazanorgsintez-E-17-Petroleum-Resin.php

Physical Properties	Metric	English	Comments
Density	>= 0.800 g/cc	>= 0.0289 lb/in³	
	@Temperature 20.0 °C	@Temperature 68.0 °F	

Thermal Properties	Metric	English	Comments
Boiling Point	>= 35.0 °C	>= 95.0 °F	Initial
	<= 220 °C	<= 428 °F	End

Component Elements Properties	Metric	English	Comments	
Free Water	<= 1.0 %	<= 1.0 %		

Descriptive Properties	Value	Comments
Appearance	Liquid from transparent to light-yellow color	

Contact Songhan Plastic Technology Co.,Ltd.

Website: www.lookpolymers.com Email: sales@lookpolymers.com

Tel: +86 021-51131842 Mobile: +86 13061808058

Skype: lookpolymers

Address: United North Road 215, Fengxian District, Shanghai City, China