

## Kazanorgsintez H Waste Diesel Fuel

Category : Fluid

**Material Notes:**

Production Method: Waste diesel oil is produced when diesel oil is used a cracked gas cooling or flushing agent in the process of ethylene production. Application: Waste diesel oil is shipped to petroleum storage and exported. Information Provided by Kazanorgsintez

Order this product through the following link:

[http://www.lookpolymers.com/polymer\\_Kazanorgsintez-H-Waste-Diesel-Fuel.php](http://www.lookpolymers.com/polymer_Kazanorgsintez-H-Waste-Diesel-Fuel.php)

Physical Properties	Metric	English	Comments
Density	$\geq 0.900 \text{ g/cc}$	$\geq 0.0325 \text{ lb/in}^3$	
	@Temperature 19.0 - 20.0 Å°C	@Temperature 66.2 - 68.0 Å°F	

Thermal Properties	Metric	English	Comments
Flash Point	$\geq 30.0 \text{ Å°C}$	$\geq 86.0 \text{ Å°F}$	determined in closed gap

Descriptive Properties	Value	Comments
Amount of impurities [pcs]	1	Mechanical impurities

## Contact Songhan Plastic Technology Co.,Ltd.

Website : [www.lookpolymers.com](http://www.lookpolymers.com)Email : [sales@lookpolymers.com](mailto:sales@lookpolymers.com)

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China