

Kazanorgsintez K-8 Waste Diesel Fuel

Category : Fluid

Material Notes:

Production Method: Waste diesel oil is produced when diesel oil is used a cracked gas cooling or flushing agent in the process of ethylene production. Application: Waste diesel oil is shipped to petroleum storage and exported. Information Provided by Kazanorgsintez

Order this product through the following link:

http://www.lookpolymers.com/polymer_Kazanorgsintez-K-8-Waste-Diesel-Fuel.php

Physical Properties	Metric	English	Comments
Density	$\geq 0.900 \text{ g/cc}$ @Temperature 19.0 - 20.0 °C	$\geq 0.0325 \text{ lb/in}^3$ @Temperature 66.2 - 68.0 °F	
Kinematic Viscosity	$\leq 12 \text{ cSt}$ @Temperature 49.9 - 50.1 °C	$\leq 12 \text{ cSt}$ @Temperature 122 - 122 °F	
Ash	$\leq 0.20 \%$	$\leq 0.20 \%$	

Thermal Properties	Metric	English	Comments
Pour Point	$\leq -10.0 \text{ }^\circ\text{C}$	$\leq 14.0 \text{ }^\circ\text{F}$	
Flash Point	$\geq 45.0 \text{ }^\circ\text{C}$	$\geq 113 \text{ }^\circ\text{F}$	determined in closed gap

Component Elements Properties	Metric	English	Comments
Free Water	$\leq 1.0 \%$	$\leq 1.0 \%$	
Sulfur, S	$\leq 0.50 \%$	$\leq 0.50 \%$	

Descriptive Properties	Value	Comments
Amount of impurities [pcs]	1	Mechanical impurities

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.comEmail : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China