

Kazanorgsintez PE80B-285D High Density Polyethylene Composite, Film Grade

Category: Polymer, Film, Thermoplastic, Polyethylene (PE), HDPE, High Density Polyethylene (HDPE), Extruded, High Density Polyethylene (HDPE), Film Grade

Material Notes:

Production Method: Compositions are achieved by ethylene copolymerization by gaseous-phase method at low pressure using complex catalysts on carrier material. Application: HDPE compositions are intended to be reprocessed by extrusion method into film, used for packing of cold food, and for other purposes. Information Provided by Kazanorgsintez

Order this product through the following link:

http://www.lookpolymers.com/polymer_Kazanorgsintez-PE80B-285D-High-Density-Polyethylene-Composite-Film-Grade.php

| Physical Properties | Metric | English | Comments |
|---------------------|----------------------|------------------------|----------|
| Density | 0.937 - 0.943 g/cc | 0.0339 - 0.0341 lb/in³ | |
| Volatiles | <= 0.090 % | <= 0.090 % | |
| Melt Flow | 0.40 - 0.80 g/10 min | 0.40 - 0.80 g/10 min | ±10% |
| Ash | <= 0.060 % | <= 0.060 % | |

| Mechanical Properties | Metric | English | Comments |
|-------------------------|-------------|-------------|----------|
| Tensile Strength, Yield | >= 16.0 MPa | >= 2320 psi | |
| Elongation at Break | >= 700 % | >= 700 % | |
| Tear Strength Test | >= 20.6 | >= 20.6 | MPa |

| Descriptive Properties | Value | Comments |
|----------------------------|-------|----------|
| Amount of impurities [pcs] | 3 | |

Contact Songhan Plastic Technology Co.,Ltd.

Website: www.lookpolymers.com Email: sales@lookpolymers.com

Tel: +86 021-51131842 Mobile: +86 13061808058

Skype: lookpolymers

Address: United North Road 215, Fengxian District, Shanghai City, China