

Kazanorgsintez Polyethyleneglycol-13

Category: Polymer, Thermoplastic, Polyethylene (PE)

Material Notes:

Production Method: Obtained by interaction of ethylene oxide with ethylene glycol. Application: PEG-13 is used as a component of part of epamine 06 preparation. Information Provided by Kazanorgsintez

Order this product through the following link:

 $http://www.lookpolymers.com/polymer_Kazanorgsintez-Polyethyleneglycol-13.php\\$

Physical Properties	Metric	English	Comments
рН	7.0 - 9.0	7.0 - 9.0	Hydrogen ions activity of aqueous solution with mass content of 1%

Component Elements Properties	Metric	English	Comments
Free Water	<= 0.30 %	<= 0.30 %	

Descriptive Properties	Value	Comments
Appearance	At 18°C to 22°C: Vaseline-like dough of light yellow color Melt Appearance: Transparent solution of light yellow color	
Color	4	Melt chromaticity by Iodine scale, mg of J2 per 100 cm3 of at 39 to 41 °C
Hydroxyl Number, mg of KOH/g of PEG-13	176-190	

Contact Songhan Plastic Technology Co.,Ltd.

Website: www.lookpolymers.com Email: sales@lookpolymers.com

Tel: +86 021-51131842 Mobile: +86 13061808058

Skype: lookpolymers

Address: United North Road 215, Fengxian District, Shanghai City, China