

## Kraton<sup>®</sup> G2832 GS-N (SEBS) Compound

Category : Polymer , Thermoplastic , Elastomer, TPE

**Material Notes:**

Description: Kraton G2832 GS-N is an easy processing, 49 Shore A hardness material designed for film applications. It is supplied from North America in the physical form identified: Kraton G2832 GS-N - supplied as a dusted, dense pelletRegion: Asia Pacific, Europe, Japan, North America, and South AmericaApplications: Adhesives, Sealant and Coatings; Bitumen Modification; Compounding and Personal Hygiene; Footwear; and Impact ModificationInformation provided by Kraton<sup>®</sup>

Order this product through the following link:

[http://www.lookpolymers.com/polymer\\_Kraton-G2832-GS-N-SEBS-Compound.php](http://www.lookpolymers.com/polymer_Kraton-G2832-GS-N-SEBS-Compound.php)

Physical Properties	Metric	English	Comments
Specific Gravity	0.910 g/cc	0.910 g/cc	ASTM D792
Melt Flow	13 - 21 g/10 min @Load 5.00 kg, Temperature 200 Å°C	13 - 21 g/10 min @Load 11.0 lb, Temperature 392 Å°F	ASTM D1238

Mechanical Properties	Metric	English	Comments
Hardness, Shore A	44 - 54	44 - 54	BAM 1003
Tensile Strength	10.42 MPa	1511 psi	ASTM D412
Elongation at Break	610 %	610 %	ASTM D412

Descriptive Properties	Value	Comments
Propagation Tear Resistance	43 gf/mil	ASTM D1922

## Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China