

Kuraray SEPTON® S8006 Thermoplastic Rubber

Category: Polymer, Thermoplastic, Elastomer, TPE, Thermoplastic Elastomer, Melt-Processible Rubber

Material Notes:

SEPTON® is a series of high performance thermoplastic rubbers developed by Kuraray Co. Ltd. using its isoprene technology. SEPTON® resins are hydrogenated styrenic block copolymers, which exhibit rubber-like properties over a wide range of temperatures. SEPTON®'s characteristics include:Excellent Mechanical PropertiesGood WeatherabilityExcellent Low Temperature PropertiesExcellent Electrical PropertiesSuperior Heat ResistanceExcellent Chemical ResistanceLow ToxicitySEPTON® grades are available with a range of Shore A hardness of 35-95 and tensile strengths of 290-5600 psi. SEPTON® resins are highly extendible with fillers, resins and oils, which allows formulation of a variety of hardness for adhesives, sealants and various compounds. As an additive, SEPTON® resins can be used to improve toughness of a variety of plastics. Several SEPTON® grades have U.S. FDA and USP Class VI approval.SEPTON® has a versatile series of grades which can be used in numerous processing techniques such as blow molding, injection molding, extrusion, hot melt and solution coatings. SEPTON® resins are thermoplastics therefore, the scrap is recyclable without significant loss of properties.Information provided by The Kuraray Group.

Order this product through the following link:

http://www.lookpolymers.com/polymer_Kuraray-SEPTON-S8006-Thermoplastic-Rubber.php

| Physical Properties | Metric | English | Comments |
|---------------------|-------------------------|--|------------------------|
| Specific Gravity | 0.920 g/cc | 0.920 g/cc | ISO 1183 |
| Viscosity | 42 cP | 42 cP | 42 cP |
| | @Temperature 30.0 °C | 5% wt Toluene Solution @Temperature 86.0 °F | 5% wt Toluene Solution |

| Chemical Properties | Metric | English | Comments |
|---------------------|--------|---------|----------|
| Styrene Content | 33 % | 33 % | |

| Descriptive Properties | Value | Comments |
|------------------------|-------|----------|
| Physical Form | Crumb | |

Contact Songhan Plastic Technology Co.,Ltd.

Website: www.lookpolymers.com Email: sales@lookpolymers.com

Tel: +86 021-51131842 Mobile: +86 13061808058

Skype: lookpolymers

Address: United North Road 215, Fengxian District, Shanghai City, China