

LG Chemical C9 Product

Category : Fluid

Material Notes:

Physical Properties: Colorless liquid similar to DIESEL oil. Obtained as a by-product from pyrolysis oil hydration plant which was produced from naphtha pyrolysis process. It is composed of hydrocarbons of C9 and higher, and the content of aromatics is high. Uses: Used as a fuel for industrial boiler. Information provided by LG Chemical

Order this product through the following link:

http://www.lookpolymers.com/polymer_LG-Chemical-C9-Product.php

Physical Properties	Metric	English	Comments
Specific Gravity	0.940 g/cc	0.940 g/cc	15.5/15.5Â°C
Viscosity	0.70 cP	0.70 cP	KSM 2014-90
	@Temperature 100 Â°C	@Temperature 212 Â°F	
	1.4 cP	1.4 cP	KSM 2014-90
	@Temperature 40.0 Â°C	@Temperature 104 Â°F	

Thermal Properties	Metric	English	Comments
Boiling Point	166 - 290 Â°C	331 - 554 Â°F	
Flash Point	93.0 Â°C	199 Â°F	

Descriptive Properties	Value	Comments
Autoignition Temperature	464-529Â°C	
Components	C6â€™s ~ C8â€™s Non aromatics	0.017
	C8â€™s Aromatics	0.007
	C9â€™s & Heavier	0.974
	Styrene	0.002
Heat Value	10240-10400 cal/g	KSM 2057-92

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215, Fengxian District, Shanghai City, China