

LG Chemical LS100S PVC

Category : Polymer , Thermoplastic , Vinyl (PVC) , PVC, Uncompounded

Material Notes:

General Description: LS100S, homopolymer made by suspension polymerization, can be applied to soft or semi-hard products. Products made from LS100S have excellent surface, bright color and transparency properties. Main Applications: High transparency soft/hard sheet, hoses, wrapping film and innocuous film. CAS No: 9002-86-2 Information provided by LG Chemical

Order this product through the following link:

http://www.lookpolymers.com/polymer_LG-Chemical-LS100S-PVC.php

Physical Properties	Metric	English	Comments
Specific Gravity	1.40 g/cc	1.40 g/cc	ASTM D790
Bulk Density	0.480 - 0.560 g/cc	0.0173 - 0.0202 lb/in ³	ASTM D1895
Volatiles	<= 0.30 % @Temperature 110 Â°C, Time 3600 sec	<= 0.30 % @Temperature 230 Â°F, Time 1.00 hour	ASTM D3030
Particle Mesh Size	45 Mesh	45 Mesh	<0.2%; ASTM D1921
Molecular Weight	60000 - 150000 g/mol	60000 - 150000 g/mol	

Thermal Properties	Metric	English	Comments
Melting Point	302 Â°C	576 Â°F	

Descriptive Properties	Value	Comments
Autoignition Temperature	435Â°C	
Degree of Polymerization	980-1080	30Â°C, JIS K 6720-2
K-Value	66	DIN53726 / ISO1628-2

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China