

## Loctite® Gasket Eliminator® 504 Flange Sealant

Category : Polymer , Adhesive , Thermoset

**Material Notes:**

Anaerobic Gasketing Loctite® 504 Gap Filling Rigid Cure Gasket Eliminator® Flange Sealant A single-component, instant low pressure seal that fills gaps to 0.030". Typical Use: Gap filling

Order this product through the following link:

[http://www.lookpolymers.com/polymer\\_Loctite-Gasket-Eliminator-504-Flange-Sealant.php](http://www.lookpolymers.com/polymer_Loctite-Gasket-Eliminator-504-Flange-Sealant.php)

Physical Properties	Metric	English	Comments
Density	1.08 g/cc	0.0390 lb/in <sup>3</sup>	
Viscosity	500000 - 1.20e+6 cP	500000 - 1.20e+6 cP	Thixotropic

Thermal Properties	Metric	English	Comments
Maximum Service Temperature, Air	149 °C	300 °F	
Minimum Service Temperature, Air	-53.9 °C	-65.0 °F	

Processing Properties	Metric	English	Comments
Cure Time	30.0 - 240 min	0.500 - 4.00 hour	Full Cure; Primed
	240 - 1440 min	4.00 - 24.0 hour	Full Cure; Unprimed

Descriptive Properties	Value	Comments
Color	Orange	
Gap Fill	0.030 in.	Unprimed
	0.05 in.	Primed

## Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China