

Loctite® Gasket Eliminator® 510 Flange Sealant

Category : Polymer , Adhesive , Thermoset

Material Notes:

Anaerobic Gasketing Loctite® 510 High Temperature Rigid Cure Gasket Eliminator® Flange Sealant Product has a temperature range to 400°F with excellent solvent and chemical resistance. Makes or dresses gaskets in rigid assemblies. Eliminates gasket compression set.

Recommended Primer: 7649 (N). UL classified Typical Use: High temperature applications, Excellent solvent resistance

Order this product through the following link:

http://www.lookpolymers.com/polymer_Loctite-Gasket-Eliminator-510-Flange-Sealant.php

Physical Properties	Metric	English	Comments
Density	1.16 g/cc	0.0419 lb/in ³	
Viscosity	188000 - 500000 cP	188000 - 500000 cP	Thixotropic

Thermal Properties	Metric	English	Comments
Maximum Service Temperature, Air	204 °C	400 °F	
Minimum Service Temperature, Air	-53.9 °C	-65.0 °F	

Processing Properties	Metric	English	Comments
Cure Time	30.0 - 240 min	0.500 - 4.00 hour	Full Cure; Primed
	240 - 1440 min	4.00 - 24.0 hour	Full Cure; Unprimed

Descriptive Properties	Value	Comments
Color	Red	
Gap Fill	0.010 in.	Unprimed
	0.02 in.	Primed

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China