

Loctite® Varidot™ 3616 Stencil Print

Category : Polymer , Adhesive , Thermoset

Material Notes:

Surface Mount Adhesives Loctite® Chipbonder® Surface Mount Adhesives (SMAs) maintain component positioning during wave solder and solder reflow processes. Loctite offers a variety of application techniques including syringe dispense, stencil print and pin transfer. Loctite® syringe dispense products provide good performance for electronics assembly: High Speed Dispense Low Temperature Cure Products for difficult-to-bond substrates Loctite® 3616 Varidot™ Stencil Print A high speed stencil printing adhesive. Rounded dot profile. Process Method: High Speed Varidot Stencil Print (Up to 6"/sec.) Storage (Protect from heat): 40°F (+/-5°F) or 5°C (+/-3°C)

Order this product through the following link:

http://www.lookpolymers.com/polymer_Loctite-Varidot-3616-Stencil-Print.php

Processing Properties	Metric	English	Comments
Cure Time	1.00 min	0.0167 hour	
	@Temperature 150 °C	@Temperature 302 °F	
	1.50 min	0.0250 hour	
	@Temperature 125 °C	@Temperature 257 °F	
Shelf Life	9.00 Month	9.00 Month	From date of manufacture

Descriptive Properties	Value	Comments
Color	Red	

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.comEmail : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215, Fengxian District, Shanghai City, China