

Lord Adhesives Flocklok® P13 Adhesive

Category : Polymer , Adhesive

Material Notes:

Flocklok® P13 is a moisture curing, flexible polyurethane adhesive used for automotive weatherstrip sealing profiles to flock. This adhesive will adhere polyester or polyamide flock to a variety of elastomers including EPDM, NR, CR, and SBR. All information provided by Lord.

Order this product through the following link:

http://www.lookpolymers.com/polymer_Lord-Adhesives-Flocklok-P13-Adhesive.php

Physical Properties	Metric	English	Comments
Specific Gravity	0.960 g/cc	0.960 g/cc	
Solids Content	45 - 50 %	45 - 50 %	
Viscosity Measurement	20 - 60	20 - 60	Seconds; Spindle #2, 30rpm; Brookfield LVT

Thermal Properties	Metric	English	Comments
Flash Point	23.0 Â°C	73.4 Â°F	Seta

Processing Properties	Metric	English	Comments
Shelf Life	6.00 Month	6.00 Month	
	@Temperature 21.0 - 27.0 Â°C	@Temperature 69.8 - 80.6 Â°F	

Descriptive Properties	Value	Comments
Appearance	Black	
Composition	Polyurethane polymer and filler dispersed in xylene and ethyl acetate	

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China