

## **Lord Adhesives HPC-6C Ethylene Acrylic Elastomer Coating**

Category: Fluid

## **Material Notes:**

LORD HPC-6B and HPC-6C are one-part, room temperature curing ethylene acrylic elastomer (AEM) coatings which feature robust adhesion and exceptional mechanical properties. These coatings enhance ozone and fluid resistance on a wide variety of substrates while having very low VOCs.HPC-6B is black; HPC-6C is clear and colorable. Coatings are composed of a mixture of polymers, organic compounds and fillers dissolved or dispersed in an organic solvent system. Additionally, the HPC-6C coating mixes well with colored pigments allowing for the creation of colored coatings.All information provided by Lord.

## Order this product through the following link:

http://www.lookpolymers.com/polymer\_Lord-Adhesives-HPC-6C-Ethylene-Acrylic-Elastomer-Coating.php

Physical Properties	Metric	English	Comments
Density	1.28 g/cc	0.0462 lb/in³	
Solids Content	10.9 %	10.9 %	by weight
	13.7 %	13.7 %	by volume
Brookfield Viscosity	50 - 300 cP	50 - 300 cP	LVT, Spindle #2 @ 30rpm
	@Temperature 25.0 °C	@Temperature 77.0 °F	

Thermal Properties	Metric	English	Comments
Flash Point	20.0 °C	68.0 °F	Seta

Processing Properties	Metric	English	Comments
Cure Time	10.0 min	0.167 hour	Let sit for 24 hours to develop a final cure
	@Temperature 121 °C	@Temperature 250 °F	
	>= 1440 min	>= 24.0 hour	
	@Temperature 25.0 °C	@Temperature 77.0 °F	
Shelf Life	12.0 Month	12.0 Month	
	@Temperature 21.0 - 27.0 °C	@Temperature 69.8 - 80.6 °F	

Descriptive Properties	Value	Comments
Appearance	Clear	
Consistency	Liquid	



Descriptive Properties Value Comments

## **Contact Songhan Plastic Technology Co.,Ltd.**

Website: www.lookpolymers.com Email: sales@lookpolymers.com

Tel: +86 021-51131842 Mobile: +86 13061808058

Skype: lookpolymers

Address: United North Road 215, Fengxian District, Shanghai City, China